



| CCA | | | | |
|---------------|-------------|--------|---------|---------|
| Guage | wire length | | | |
| | 0-5ft | 5-10ft | 10-15ft | 15-20ft |
| 8AWG | 175 | 87 | 58 | 45 |
| 4AWG | 442 | 222 | 149 | 112 |
| 2AWG | 710 | 354 | 237 | 178 |
| 1/OAWG | 1133 | 567 | 378 | 283 |
| OVERSIZE OAWG | 1253 | 627 | 420 | 298 |

| OFC | | | | |
|---------------|-------------|--------|---------|---------|
| Guage | wire length | | | |
| | 0-5ft | 5-10ft | 10-15ft | 15-20ft |
| 8AWG | 215 | 100 | 67 | 55 |
| 4AWG | 512 | 251 | 171 | 145 |
| 2AWG | 845 | 410 | 279 | 234 |
| 1/OAWG | 1345 | 669 | 445 | 320 |
| OVERSIZE OAWG | 1495 | 750 | 493 | 345 |

This page shows the recommended maximum current that should be fed through our Bassface OFC and CCA blended power and earth cable, at 12V nominal.

Please adhere to our recommendations and ensure that all connections are made professionally and carefully to ensure reliable and safe operation.

Best wishes,

Team Bassface Worldwide