



BASSFACE

TEAMTW / NEOONE

The TeamTW/NeoOne is our latest generation high performance neodymium tweeter. Featuring a large voice coil, high sensitivity and wide response with outstanding high frequency detail.

DETAILED TECHNICAL DATA

Power Handling [Per Driver]:	120WRMS [Xover @ 4KHz/12Db Oct]
Nominal Impedance:	8ohms
DC Impedance:	6.3ohms
S.P.L: [1W/1M]:	106 DB
Voice coil:	32.4mm
Magnet:	32mm x 16mm x 7mm
Frequency Response:	1KHz > 20KHz
Magnet Type:	N40 Neodymium

TEAM TIPS


- We recommend to locate all tweeters per a channel close to each other to reduce phase issues.
- Ensure that any capacitors in your crossover unit are at least 50v rated [lower voltage capacitors provide less protection to hard driven tweeters 50v 5.3uf capacitor and a 0.25mh inductor for 5 kHz basic crossover]
- Never use a full range signal to power the tweeters, Reduce the crossover point at your own risk.

UPC: 685757152297
EAN: 6857571522974
PRINTED: 6857571522974



TECHNICAL DRAWING

Total Diameter	100.5mm
Assembly Size	4.5mm x 3mm x 92mm
Material	Aluminum
Weight Approx [Per a Driver]	56 grams



FREQUENCY VS S.P.L.

Black: 0* Grey: 45*

